

## **ENGINEROOM CLEANER ZI-14**



## BRUKSOMRÅDER:

Extremely concentrated, alkaline cleaner for industrial purposes. It is excellent for removal of mineral oils, greases and other industrial contaminations. By breaking down the surface tension, contaminations are quickly and effectively loosened from the surface, after which they are easily flushed with water. The product does not cause stable emulsions, separates quickly and will not cause disturbance in oil/water separators. May be applied with all types of equipment. The biodegradability of the surface active agents used in this product satisfies the Detergents Regulation (EC 648 / 2004).



## **DOSERING:**

When using the product the first time, it is recommanded to do some tests on a less visible spot. Dilution ratios depend on type and amount of contamination, equipment used, as well as water temperature and pressure. The product may be diluted up to max. 1:30 with water. Apply to the object to be cleaned, allow to work for some time (do not let dry!), then flush with plenty of water.







## TEKNISK DATA OG LAGRING:

**FARGE** GJENNOMSIKTIG


FORM VÆSKE MINIMUM BRUKSTEMPERATUR +5°C MAKSIMUM BRUKSTEMPERATUR +80°C

VENNLIGST REFERER TIL TEKNISK/HMS DATABLAD FOR MER INFORMASJON.



Disclaimer | In the event of an emergency please consult the MSDS. Although we do our best to ensure all supplied information is complete and correct, we are not responsible in the event of emergencies.

RÅD | ADVICE



min.. 5 - 10



3 % - 10%





Product nr. **71015** 

Date of creation: 15-02-2024 | Version: 1 | Last adjustment: 15-02-2024